

This Page Is Inserted by IFW Operations
and is not a part of the Official Record

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images may include (but are not limited to):

- BLACK BORDERS
- TEXT CUT OFF AT TOP, BOTTOM OR SIDES
- FADED TEXT
- ILLEGIBLE TEXT
- SKEWED/SLANTED IMAGES
- COLORED PHOTOS
- BLACK OR VERY BLACK AND WHITE DARK PHOTOS
- GRAY SCALE DOCUMENTS

IMAGES ARE BEST AVAILABLE COPY.

**As rescanning documents *will not* correct images,
please do not report the images to the
Image Problem Mailbox.**

INTERNET COOPERATION TREATY

PCT

NOTIFICATION OF ELECTION

(PCT Rule 61.2)

From the INTERNATIONAL BUREAU

To:

Assistant Commissioner for Patents
United States Patent and Trademark
Office
Box PCT
Washington, D.C.20231
ÉTATS-UNIS D'AMÉRIQUE

in its capacity as elected Office

Date of mailing (day/month/year) 15 December 1999 (15.12.99)	
International application No. PCT/GB99/01394	Applicant's or agent's file reference J00040649WO
International filing date (day/month/year) 05 May 1999 (05.05.99)	Priority date (day/month/year) 05 May 1998 (05.05.98)
Applicant TITMUSS, Richard, John et al	

1. The designated Office is hereby notified of its election made:

☒ in the demand filed with the International Preliminary Examining Authority on:

11 November 1999 (11.11.99)

☐ in a notice effecting later election filed with the International Bureau on:

2. The election ☒ was

☐ was not

made before the expiration of 19 months from the priority date or, where Rule 32 applies, within the time limit under Rule 32.2(b).

<p>The International Bureau of WIPO 34, chemin des Colombettes 1211 Geneva 20, Switzerland</p> <p>Facsimile No.: (41-22) 740.14.35</p>	<p>Authorized officer</p> <p>Jean-Marc Vivet</p> <p>Telephone No.: (41-22) 338.83.38</p>
--	--

PCT

INTERNATIONAL SEARCH REPORT

(PCT Article 18 and Rules 43 and 44)

Applicant's or agent's file reference J00040649W0	FOR FURTHER ACTION see Notification of Transmittal of International Search Report (Form PCT/ISA/220) as well as, where applicable, item 5 below.	
International application No. PCT/GB 99/ 01394	International filing date (day/month/year) 05/05/1999	(Earliest) Priority Date (day/month/year) 05/05/1998
Applicant BRITISH TELECOMMUNICATIONS PUBLIC LIMITED COMPANY		

This International Search Report has been prepared by this International Searching Authority and is transmitted to the applicant according to Article 18. A copy is being transmitted to the International Bureau.

This International Search Report consists of a total of 4 sheets.

☒ It is also accompanied by a copy of each prior art document cited in this report.

1. Basis of the report

- a. With regard to the **language**, the international search was carried out on the basis of the international application in the language in which it was filed, unless otherwise indicated under this item.

☐ the international search was carried out on the basis of a translation of the international application furnished to this Authority (Rule 23.1(b)).

- b. With regard to any **nucleotide and/or amino acid sequence** disclosed in the international application, the international search was carried out on the basis of the sequence listing :

☐ contained in the international application in written form.

☐ filed together with the international application in computer readable form.

☐ furnished subsequently to this Authority in written form.

☐ furnished subsequently to this Authority in computer readable form.

☐ the statement that the subsequently furnished written sequence listing does not go beyond the disclosure in the international application as filed has been furnished.

☐ the statement that the information recorded in computer readable form is identical to the written sequence listing has been furnished

2. ☐ **Certain claims were found unsearchable** (See Box I).

3. ☐ **Unity of invention is lacking** (see Box II).

4. With regard to the **title**,

☒ the text is approved as submitted by the applicant.

☐ the text has been established by this Authority to read as follows:

5. With regard to the **abstract**,

☒ the text is approved as submitted by the applicant.

☐ the text has been established, according to Rule 38.2(b), by this Authority as it appears in Box III. The applicant may, within one month from the date of mailing of this international search report, submit comments to this Authority.

6. The figure of the **drawings** to be published with the abstract is Figure No.

☒ as suggested by the applicant.

☐ because the applicant failed to suggest a figure.

☐ because this figure better characterizes the invention.

1

☐ None of the figures.

INTERNATIONAL SEARCH REPORT

National Application No

GB 99/01394

A. CLASSIFICATION OF SUBJECT MATTER

IPC 6 G09B29/00 G06T17/50 G08G1/0969

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 6 G06F G06T G09B G01C G08G

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category °	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
Y	EP 0 436 263 A (DELORME DAVID M) 10 July 1991 (1991-07-10) page 9, line 24 - page 10, line 34; figures 4-8 --- -/--	1-17, 24-26



Further documents are listed in the continuation of box C.



Patent family members are listed in annex.

° Special categories of cited documents :

- "A" document defining the general state of the art which is not considered to be of particular relevance
- "E" earlier document but published on or after the international filing date
- "L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- "O" document referring to an oral disclosure, use, exhibition or other means
- "P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.

"&" document member of the same patent family

Date of the actual completion of the international search

2 August 1999

Date of mailing of the international search report

17/08/1999

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
Fax: (+31-70) 340-3016

Authorized officer

Deane, E

INTERNATIONAL SEARCH REPORT

International Application No

/GB 99/01394

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
Y	<p>ZHANG L., ET AL.: "A client/server approach to 3D modeling support system for coast change study"</p> <p>GIS/LIS '96 ANNUAL CONF. AND EXPOSITION PROC., PROC. OF GEOGRAPHIC INFORMATION SYSTEMS/LAND INFORMATION SYSTEMS, 19 - 21 November 1996, pages 1265-1274, XP002111059</p> <p>Denver, CO, USA</p> <p>& DATABASE INSPEC 'Online!</p> <p>INSTITUTE OF ELECTRICAL ENGINEERS, STEVENAGE, GB</p> <p>Inspec No. 6264890, abstract</p> <p>---</p>	1-22, 24-26
Y	<p>KUNIHIRO ISHIKAWA ET AL: "MAP NAVIGATION SOFTWARE OF THE ELECTRO-MULTIVISION OF THE '91 TOYOTA SOARER"</p> <p>PROCEEDINGS OF THE VEHICLE NAVIGATION AND INFORMATION SYSTEMS CONFERENCE, DEARBORN, OCT. 20 - 23, 1991, vol. 1, 20 October 1991 (1991-10-20), pages 463-473, XP000347114</p> <p>INSTITUTE OF ELECTRICAL AND ELECTRONICS ENGINEERS ISBN: 0-7803-0488-8</p> <p>page 464, right-hand column, line 1 - page 466, left-hand column, line 17; figures 3-5</p> <p>---</p>	1-17,25
Y	<p>US 4 972 319 A (DELORME DAVID M)</p> <p>20 November 1990 (1990-11-20)</p> <p>column 11, line 61 - column 14, line 24; figures 8,9A,9B</p> <p>---</p>	1-10
Y	<p>EP 0 798 539 A (SANYO ELECTRIC CO ;TOKYO SANYO ELECTRIC CO (JP))</p> <p>1 October 1997 (1997-10-01)</p> <p>column 10, line 54 - column 12, line 8; figure 4</p> <p>---</p>	18-22
A	<p>US 5 448 696 A (SHIMADA SHIGERU ET AL)</p> <p>5 September 1995 (1995-09-05)</p> <p>column 11, line 56 - column 12, line 7; figure 20</p> <p>column 3, line 17 - line 68</p> <p>---</p>	1,6,8,25
A	<p>CHANG S-K ET AL: "Pictorial Database Systems"</p> <p>COMPUTER, vol. 14, no. 11, 1 November 1981 (1981-11-01), pages 13-21, XP002078619</p> <p>ISSN: 0018-9162</p> <p>page 14, left-hand column, line 3 - page 15, left-hand column, line 43</p> <p>---</p>	1,6,8,25
	<p>---</p> <p>-/--</p>	

INTERNATIONAL SEARCH REPORT

International Application No

/GB 99/01394

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	<p>WO 96 07110 A (MANNINGS ROBIN THOMAS ;BRITISH TELECOMM (GB); WALL NIGEL DAVID CHA) 7 March 1996 (1996-03-07) cited in the application abstract; figure 1 -----</p>	18

INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

GB 99/01394

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
EP 0436263	A	10-07-1991	US 4972319 A	20-11-1990
			US 5030117 A	09-07-1991

US 4972319	A	20-11-1990	EP 0436263 A	10-07-1991
			US 5030117 A	09-07-1991


EP 0798539	A	01-10-1997	JP 9264747 A	07-10-1997
			JP 10213444 A	11-08-1998
			JP 9269237 A	14-10-1997
			JP 9269238 A	14-10-1997
			JP 9269234 A	14-10-1997
			JP 9269235 A	14-10-1997

US 5448696	A	05-09-1995	JP 2865855 B	08-03-1999
			JP 4204480 A	24-07-1992
			JP 2865856 B	08-03-1999
			JP 4204481 A	24-07-1992

WO 9607110	A	07-03-1996	AU 684228 B	04-12-1997
			AU 3393195 A	22-03-1996
			AU 695816 B	20-08-1998
			AU 5538998 A	23-04-1998
			CA 2198886 A	07-03-1996
			DE 69506563 D	21-01-1999
			DE 69506563 T	06-05-1999
			EP 0777863 A	11-06-1997
			EP 0837341 A	22-04-1998
			ES 2126931 T	01-04-1999
			FI 970848 A	28-02-1997
			JP 10505420 T	26-05-1998
			NO 970940 A	28-02-1997
			NZ 292210 A	28-07-1998
			NZ 329889 A	28-05-1999

INTERNATIONAL PRELIMINARY EXAMINATION REPORT

(PCT Article 36 and Rule 70)

Applicant's or agent's file reference J00040649WO		FOR FURTHER ACTION See Notification of Transmittal of International Preliminary Examination Report (Form PCT/IPEA/416)	
International application No. PCT/GB99/01394	International filing date (day/month/year) 05/05/1999	Priority date (day/month/year) 05/05/1998	
International Patent Classification (IPC) or national classification and IPC G09B29/00			
Applicant BRITISH TELECOMMUNICATIONS PUBLIC LIMITED COMPANY			
<p>1. This international preliminary examination report has been prepared by this International Preliminary Examining Authority and is transmitted to the applicant according to Article 36.</p> <p>2. This REPORT consists of a total of 6 sheets, including this cover sheet.</p> <p><input checked="" type="checkbox"/> This report is also accompanied by ANNEXES, i.e. sheets of the description, claims and/or drawings which have been amended and are the basis for this report and/or sheets containing rectifications made before this Authority (see Rule 70.16 and Section 607 of the Administrative Instructions under the PCT).</p> <p>These annexes consist of a total of 6 sheets.</p>			
<p>3. This report contains indications relating to the following items:</p> <p>I <input checked="" type="checkbox"/> Basis of the report</p> <p>II <input type="checkbox"/> Priority</p> <p>III <input type="checkbox"/> Non-establishment of opinion with regard to novelty, inventive step and industrial applicability</p> <p>IV <input type="checkbox"/> Lack of unity of invention</p> <p>V <input checked="" type="checkbox"/> Reasoned statement under Article 35(2) with regard to novelty, inventive step or industrial applicability; citations and explanations supporting such statement</p> <p>VI <input type="checkbox"/> Certain documents cited</p> <p>VII <input checked="" type="checkbox"/> Certain defects in the international application</p> <p>VIII <input type="checkbox"/> Certain observations on the international application</p>			
Date of submission of the demand 11/11/1999		Date of completion of this report 11.08.00	
Name and mailing address of the international preliminary examining authority:  European Patent Office D-80298 Munich Tel. +49 89 2399 - 0 Tx: 523656 epmu d Fax: +49 89 2399 - 4465		Authorized officer Watson, S Telephone No. +49 89 2399 2840	



**INTERNATIONAL PRELIMINARY
EXAMINATION REPORT**

International application No. PCT/GB99/01394

I. Basis of the report

1. This report has been drawn on the basis of *(substitute sheets which have been furnished to the receiving Office in response to an invitation under Article 14 are referred to in this report as "originally filed" and are not annexed to the report since they do not contain amendments.)*:

Description, pages:

1-33 as originally filed

Claims, No.:

1-26 as received on 26/07/2000 with letter of 24/07/2000

Drawings, sheets:

1/10-10/10 as originally filed

2. The amendments have resulted in the cancellation of:

- ☐ the description, pages:
☐ the claims, Nos.:
☐ the drawings, sheets:

3. ☐ This report has been established as if (some of) the amendments had not been made, since they have been considered to go beyond the disclosure as filed (Rule 70.2(c)):

4. Additional observations, if necessary:

**INTERNATIONAL PRELIMINARY
EXAMINATION REPORT**

International application No. PCT/GB99/01394

V. Reasoned statement under Article 35(2) with regard to novelty, inventive step or industrial applicability; citations and explanations supporting such statement

1. Statement

Novelty (N)	Yes:	Claims	1-26
	No:	Claims	
Inventive step (IS)	Yes:	Claims	1-26
	No:	Claims	
Industrial applicability (IA)	Yes:	Claims	1-26
	No:	Claims	

2. Citations and explanations

see separate sheet

VII. Certain defects in the international application

The following defects in the form or contents of the international application have been noted:

see separate sheet

**INTERNATIONAL PRELIMINARY
EXAMINATION REPORT - SEPARATE SHEET**

International application No. PCT/GB99/01394

V Reasoned statement under Article 35(2) with regard to novelty, inventive step or industrial applicability; citations and explanations supporting such statement

1 The subject-matter of claims 1, 6, 8, 17, 18 and 25 is considered to be new, as it is not known from the prior art to provide methods and apparatuses for storing location-based information where indexing nodes are responsible for a predefined locality and information sources are indexed to these nodes, whereby the indexing nodes are distributed amongst a distributed network of data storage devices accessible simultaneously for users at a plurality of remote user devices.

2.1 Document EP 0 436 263 (D1) is taken as being the closest prior art for claims 1 and 25. This document shows a method of storing and/or retrieving location-based information (see abstract), comprising storing indexing data respectively representing different ones of a plurality of first localities in relation to which information storage is accessible (see page 9, lines 24-27 and figure 8 - the quadrant files are regarded as being the first localities); and selecting ones of said first nodes to represent second localities for which information is to be stored and/or retrieved such that:
said first and second localities bear a predetermined locational relationship (the first localities are a predetermined geographical area with respect to the locational data they are representing);
said first and second localities bear a predetermined relationship in size (the first localities represent specific scaling down of the second localities, see figure 8).

D1 further shows an apparatus for storing location-based information, said apparatus comprising means for storing indexing data defining indexing nodes which are referentially interlinked (page 9, lines 24-41), each said indexing node being provisioned with a locality for which it is responsible and means for comparing the size of an input locality in relation to which information storage is to be accessed and a locality for which an indexing node is responsible (page 10, lines 3-18).

The subject-matter of claims 1 and 25 differs from this known subject-matter in that the indexing nodes are distributed amongst a distributed network of data storage devices accessible simultaneously for users at a plurality of remote user devices.

The problem to be solved by this invention is regarded as being to allow fast simultaneous access to multiple users.

The solution proposed in claims 1 and 25 is considered to be inventive as although distributed data storage networks are well-known, it is not known from the available prior art to also distribute indexing nodes across the network.

- 2.2 Document EP 0 798 539 (D5) is taken as being the closest prior art for claims 6, 8 and 18. This document shows a method of storing location based information, the method comprising: defining a plurality of indexing nodes each of which is responsible for a predefined locality (using indexing nodes is well known in the art and implicitly in D5 within the disc the data is stored in a "node" structure), said plurality of nodes including a higher level node responsible for a larger locality and lower level nodes responsible for smaller localities which overlap said larger locality (see column 13, lines 19-24), indexing references to information sources containing locality-specific information at said data access nodes, different information source references being indexed at said higher level node than at said lower level nodes (column 13, lines 24-31); and transmitting said references from said indexing nodes on request (col. 13, line 59 - col. 14, line 9). It is also known from D5 that one or more of said references is repeatedly indexed at different nodes (any reference to a road passing through a primary part and a secondary part will be indexed in both).

Document D5 also discloses a method of retrieving information for presentation to a user, the method comprising: defining a locality of interest to the user in dependence on both a location of the user and a speed of travel of the user (see col. 11, line 47-col. 12, line 8); and selecting indexing nodes from which locality-specific information may be retrieved, on the basis of the defined locality of interest (col. 13, lines 24-26).

The subject-matter of claims 6, 8 and 18 differs from this known subject-matter in that the indexing nodes are distributed amongst a distributed network of data storage devices accessible simultaneously for users at a plurality of remote user devices.

For the reasons outlined in paragraph 2.1 above, the subject-matter of claims 6, 8

**INTERNATIONAL PRELIMINARY
EXAMINATION REPORT - SEPARATE SHEET**

International application No. PCT/GB99/01394

and 18 is regarded as being inventive.

2.3 The subject-matter of claim 17 is also regarded as being inventive as it is directed to an apparatus for storing location based information according to the method of claims 1-18.

2.4 Claims 2-5, 7, 9-16, 19-24 and 26 are dependent on one of claims 1, 6, 8, 18 or 25 and therefore also fulfil the requirements of the PCT with regard to novelty and inventive step.

VII Certain defects in the international application

- 1 The features of the claims are not provided with reference signs placed in parentheses (Rule 6.2(b) PCT).
- 2 The description is not in conformity with the claims as required by Rule 5.1(a)(iii) PCT.

CLAIMS

1. A method of storing and/or retrieving location-based information, the method comprising:

storing, in a distributed network of data storage devices accessible
5 simultaneously from a plurality of remote user terminals, data defining a plurality of first localities in relation to which information storage is accessible; and

selecting ones of said first localities to represent second localities for which information is to be stored and/or retrieved such that:

i) said first and second localities bear a predetermined locational
10 relationship; and

ii) said first and second localities bear a predetermined relationship in size.

2. A method according to claim 1, wherein said first localities are
15 selected such that said first and second localities share at least one geographical location.

3. A method according to claim 1 or 2, wherein said first localities are selected such that said first and second localities are similar in size.

20

4. A method according to claim 1, 2 or 3, wherein said data defines access nodes which include a node representing a relatively large locality and one or more nodes representing one or more relatively small localities which overlap said relatively large locality.

25

5. A method according to claim 4, wherein a plurality of said nodes representing relatively small localities form divisions of said relatively large locality.

6. A method of storing location-based information, the method
5 comprising:

defining, in a distributed network of data storage devices accessible simultaneously from a plurality of user terminals, a plurality of data access nodes each of which is responsible for a predefined locality, said plurality of nodes including a higher level node responsible for a larger locality and lower level nodes
10 responsible for smaller localities which overlap said larger locality,

indexing references to information sources containing locality-specific information at said data access nodes, different information source references being indexed at said higher level node than at said lower level nodes; and

transmitting said references from said data access nodes on request.
15

7. A method according to claim 6, wherein at least one information source reference is commonly indexed at said higher level node and said lower level nodes.

20 8. A method of storing location-based information, the method comprising:

defining, in a distributed network of data storage devices accessible simultaneously from a plurality of user terminals, a plurality of data access nodes each of which are responsible for a predefined locality;

indexing references to information sources containing locality-specific information at said data access nodes, one or more of such references being repeatedly indexed at different of said nodes; and

transmitting said references from said data access nodes on request.

5

9. A method according to any of claims 4 to 8, wherein said nodes are interlinked in a network structure.

10. A method according to claim 9, wherein said network structure is a hierarchical structure.

11. A method according to claim 10, wherein said nodes are interlinked in parent/child relationships.

12. A method according to claim 10 or 11, wherein said nodes are interlinked in sibling relationships.

13. A method according to claim 10, 11 or 12, wherein said nodes are interlinked in uncle/nephew relationships.

20

14. A method according to claim 10, 11, 12 or 13, wherein said nodes are interlinked in cousin/cousin relationships.

15. A method according to any of claims 11 to 14, wherein said interlinking comprises a node holding a reference whereby the related node may be accessed.

5 16. A method according to any of claims 4 to 15, wherein said nodes are distributed amongst said data storage devices.

17. Apparatus for storing location-based information in accordance with the method of any of claims 1 to 16.

10

18. A method of retrieving information for presentation to a user, the method comprising:

defining a locality of interest to the user in dependence on both a location of the user and a speed of travel of the user; and

15 selecting, in a distributed network of data storage devices accessible simultaneously from a plurality of user terminals, information sources from which locality-specific information may be retrieved, on the basis of the defined locality of interest.

20 19. A method according to claim 18, wherein the extent of the locality of interest of the user is altered in dependence on the speed of travel.

20. A method according to claim 19, wherein the extent of the locality of interest increases with the speed of travel.

25

21. A method according to any of claims 18 to 20, wherein the locality of interest is altered in dependence on the direction of travel of the user.

22. A method according to any of claims 18 to 21, comprising deriving
5 parameters relating to the travel of the user from a positioning signal receiver travelling with the user.

23. A method according to any of claims 18 to 22, comprising performing said selection in the apparatus of claim 17.

10

24. A method according to any of claims 1 to 16 or 18 to 23, wherein said network of data storage devices comprises a plurality of servers interconnected by data links and forming a distributed processing environment.

15 25. Apparatus for storing location-based information, said apparatus comprising a distributed network of data storage devices accessible simultaneously from a plurality of user terminals and defining data access nodes which are referentially interlinked, each said data access node being provisioned with a locality for which it is responsible and means for comparing the size of an input
20 locality in relation to which information storage is to be accessed and a locality for which the node is responsible.

26. Apparatus according to claim 25, wherein said apparatus is reconfigurable by the addition of, or the removal of, one or more of said data

access nodes, so as to transfer responsibility from or to one or more other nodes with localities of responsibility sharing at least one geographical location.

ABSTRACT

A method of storing and/or retrieving location-based information, the method
5 comprising:

storing, in a distributed network of data storage devices accessible
simultaneously from a plurality of remote user terminals, data defining a plurality of
first localities in relation to which information storage is accessible; and

selecting ones of said first localities to represent second localities for
10 which information is to be stored and/or retrieved such that:

i) said first and second localities bear a predetermined locational
relationship; and

ii) said first and second localities bear a predetermined relationship in
size.


15



INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁶ : G09B 29/00, G06T 17/50, G08G 1/0969		A1	(11) International Publication Number: WO 99/57700
			(43) International Publication Date: 11 November 1999 (11.11.99)
(21) International Application Number: PCT/GB99/01394		(81) Designated States: JP, US, European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE).	
(22) International Filing Date: 5 May 1999 (05.05.99)			
(30) Priority Data: 9809600.1 5 May 1998 (05.05.98) GB 98303520.5 5 May 1998 (05.05.98) EP		Published With international search report. With amended claims.	
(71) Applicant (for all designated States except US): BRITISH TELECOMMUNICATIONS PUBLIC LIMITED COMPANY [GB/GB]; 81 Newgate Street, London EC1A 7AJ (GB).			
(72) Inventors; and (75) Inventors/Applicants (for US only): TITMUSS, Richard, John [GB/GB]; 27 King Edward Road, Ipswich (GB). BROOKLAND, Alan, Richard [GB/GB]; 140 Lacey Street, Ipswich IP4 2PL (GB). PLASSE, Delphine [FR/GB]; Flat 7, 15 Orwell Place, Ipswich IP4 1BD (GB). MOORE, Robert, Peter [GB/GB]; 140 High Street, Wickham Market, Suffolk IP13 0Q7 (GB).			
(74) Agents: SPAARGAREN, Jerome et al.; R.G.C. Jenkins & Co., 26 Caxton Street, London SW1H 0RJ (GB).			

(54) Title: STORAGE AND RETRIEVAL OF INFORMATION



(57) Abstract

A method of storing and/or retrieving location-based information, the method comprising: storing, in a distributed network of data storage devices accessible simultaneously from a plurality of remote user terminals, data defining a plurality of first localities in relation to which information storage is accessible; and selecting ones of said first localities to represent second localities for which information is to be stored and/or retrieved such that: i) said first and second localities bear a predetermined locational relationship; and ii) said first and second localities bear a predetermined relationship in size.

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece			TR	Turkey
BG	Bulgaria	HU	Hungary	ML	Mali	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MN	Mongolia	UA	Ukraine
BR	Brazil	IL	Israel	MR	Mauritania	UG	Uganda
BY	Belarus	IS	Iceland	MW	Malawi	US	United States of America
CA	Canada	IT	Italy	MX	Mexico	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NE	Niger	VN	Viet Nam
CG	Congo	KE	Kenya	NL	Netherlands	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NO	Norway	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	NZ	New Zealand		
CM	Cameroon			PL	Poland		
CN	China	KR	Republic of Korea	PT	Portugal		
CU	Cuba	KZ	Kazakstan	RO	Romania		
CZ	Czech Republic	LC	Saint Lucia	RU	Russian Federation		
DE	Germany	LI	Liechtenstein	SD	Sudan		
DK	Denmark	LK	Sri Lanka	SE	Sweden		
EE	Estonia	LR	Liberia	SG	Singapore		

STORAGE AND RETRIEVAL OF INFORMATION

This invention relates to the location-dependent storage and retrieval of information. The invention also relates to apparatus and methods for transmitting
5 information to mobile and roaming users in a telecommunications system.

In conventional telecommunications, a given user is associated with a given telecommunications terminal (e.g. a conventional telephone, or a computer with a modem, or a facsimile unit). However, more recently, users have become mobile. In addition to mobile telephones (for example digital cellular telephones such as those
10 conforming to the GSM standard) other types of portable terminal include pagers (either tone pagers or message pagers which can receive short textual messages and display them); so called "personal digital assistants" (PDA's) and portable facsimile or computer units adapted to communicate via cellular networks using dedicated modems. Users may also move to and from fixed terminals.

15 At the same time, the volume and types of formats of information which can be transmitted is increasing, and new, so called "multi-media" formats, consisting of single sets of information presented in multiple media (such as for example image, text and audio files) are entering use. An increasing volume of such information is available via the World Wide Web ("the Web").

20 The telecommunications channels through which information is delivered comprise channels of varying bandwidth, including optical fibre links; coaxial copper links; conventional subscriber telephone lines; infra-red local area networks; and radio frequency channels. Of these, radio frequency channels especially are used for mobile communications, although in certain areas infra red links are possible.
25 However, radio frequency channels which are used in mobile communications

generally have available the lowest bandwidth due to demands on the RF spectrum and to the channel conditions within the RF spectrum. Thus the amount of information which a mobile user on a radio frequency link can currently receive and select from is relatively limited.

5 European patent application EP-A-0718784 describes a system for retrieving information based on a user-defined profile. A server acting on behalf of the client identifies information on the basis of the user-defined profile, to generate a personalised newspaper which is delivered to the user. This provides for an automatic sorting of the large volume of data available on the World Wide Web to
10 generate a subset of the information available which is tailored to a users specific interest. However, the system is only used for providing a personalised newspaper delivered in electronic form to a static user.

 International patent publication No WO94/30023 describes a GSM telecommunications system whereby data records may be downloaded onto
15 subscriber identity modules in the system by broadcasting the data to a subscriber. The distribution of messages to subscriber identity modules in a specific area is possible, for example for advertising purposes. However, only a limited amount of data can be broadcast in such a manner for storage on the subscriber identity modules.

20 International patent publication No WO93/01665 describes a telecommunications system in which mobile users are able to receive localised information data from base stations in the system. Each base station is provided with a localised information database, containing information pertaining to the local area, which can be received by a mobile user being served by the base station on
25 request. The user is able to download selected portions of the information contained

in the localised information database by stating selections on a mobile terminal. However, the amount of information available to the user is limited to that stored in the localised information database. Furthermore, all mobile users in a cell receive the same information, and the information is localised only to the extent that the base
5 stations are separated.

International patent publication no. WO96/07110 describes a navigation information system whereby route guidance information, or possibly other locality-dependent information, may be provided to a user of a cellular telephone network. The user, on requesting service, identifies a destination, which a server specifically
10 allocated to that user uses to formulate a route. The cellular telephone of the user automatically signals tracking information to the server as the user travels. When the user's position falls within predefined "overlay areas", messages directing the user along the route are automatically generated and transmitted the cellular telephone of the user. This document describes the possibility of providing other
15 locality-dependent information, such as information about local facilities, tourist attractions, weather forecasts and public transport information.

Our earlier international application PCT/GB96/00252, published 15 August 1996, describes a multimedia telecommunications system employing reconfigurable agents. Aspects of this document are incorporated herein by reference.

20 Our earlier international application PCT/GB97/00890, published 9 October 1997, describes a telecommunication system in which a user is tracked, and the identity of a terminal which he may at any time be using is stored. The capabilities (i.e. formats in which signals can be accepted and/or output) of terminal equipment in the vicinity of the user is stored. Therefore, rather than attempting
25 (unsuccessfully) to deliver a high bandwidth signal to a low bandwidth mobile

terminal, the system directs the signal to a nearby terminal which can support a better representation of the signal. The nearby terminal may accept and output the signal in its original form, or the network may convert the signal to a different format which can be accepted by the nearby terminal.

5 Our earlier international application PCT/GB98/01056, published 22 October, 1998, describes a telecommunications system in which a location directory stores location-dependent data identifying information sources which are associated with individually defined localities. The data is accessed by a personal agent which filters the data using preference data and presents a shortlist of information sources which
10 are relevant in the locality of the user.

A paper entitled Knowledge and Location, Isabel Novoa, Mark Wilby, presented at International Joint Conference on Artificial Intelligence, Montreal, 1995, describes a model for the management of information in a distributed environment. The model proposed is a flexible addressing system based on a tree-like nodal
15 network, representing a distributed database. In order to locate information within the database, routing information is provided by nodes within the network. If a node receives a request for routing information, it first checks a database local to the node to determine whether the requested information is present. If not, the request is passed to a parent of the node. If the information is present, the routing request
20 may be passed to a destination child node whereby eventually the address required is found. The system is implemented in order to allow disassociation between the address of a mobile user, and the routing information whereby the address may be accessed.

In accordance with one aspect of the invention there is provided a method
25 of storing and/or retrieving location-based information, the method comprising:

storing, in a distributed network of data storage devices accessible simultaneously from a plurality of remote user terminals, data defining a plurality of first localities in relation to which information storage is accessible; and

selecting ones of said first localities to represent second localities for
5 which information is to be stored and/or retrieved such that:

i) said first and second localities bear a predetermined locational relationship; and

ii) said first and second localities bear a predetermined relationship in size.

10 This aspect allows the level of generality of information being stored and/or retrieved, by means of the accessible information storage, to be appropriate to the second localities. The second localities may on the one hand be a locality of interest, where information is to be retrieved, or on the other hand, a locality of pertinence, where the information is to be stored.

15 In accordance with a further aspect of the invention there is provided a method of storing location-based information, the method comprising:

defining, in a distributed network of data storage devices accessible simultaneously from a plurality of user terminals, a plurality of data access nodes each of which is responsible for a predefined locality, said plurality of nodes
20 including a higher level node responsible for a larger locality and lower level nodes responsible for smaller localities which overlap said larger locality,

indexing references to information sources containing locality-specific information at said data access nodes, different information source references being indexed at said higher level node than at said lower level nodes; and

25 transmitting said references from said data access nodes on request.

In accordance with a yet further aspect of the invention there is provided a method of storing location-based information, the method comprising:

defining, in a distributed network of data storage devices accessible simultaneously from a plurality of user terminals, a plurality of data access nodes
5 each of which are responsible for a predefined locality;

indexing references to information sources containing locality-specific information at said data access nodes, one or more of such references being repeatedly indexed at different of said nodes; and

transmitting said references from said data access nodes on request.

10 With different information source references indexed at higher level nodes than at lower level nodes, different references may be accessed in dependence on the locational generality of the information required.

With information source references repeatedly indexed at different of the nodes, it is possible to ensure that information sources of a given locality of
15 pertinence are appropriately indexed in relation to various fixed levels and/or localities.

In accordance with a further aspect of the invention there is provided a method of retrieving information for presentation to a user, the method comprising:

defining a locality of interest to the user in dependence on both a location
20 of the user and a speed of travel of the user; and

selecting, in a distributed network of data storage devices accessible simultaneously from a plurality of user terminals, information sources from which locality-specific information may be retrieved, on the basis of the defined locality of interest.

By taking into account the speed of travel of the user in defining the locality of interest when selecting information sources, it is possible to prevent the user being overwhelmed with large quantities of information when travelling at a relatively high speed, whilst providing the user with sufficient specificity of information when stationary or travelling at a low speed.

Furthermore, relatively remote locations of interest which are predicted to be of interest to the user on the basis of the user's speed may be included in the locality of interest.

Further aspects, features and advantages of the present invention will be apparent from the following description of preferred embodiments of the invention, which is by way of example only and which refers to the accompanying drawings, in which:-

Figure 1 is a schematic diagram illustrating the physical, or transport, layer of a telecommunications system;

Figure 2 is a schematic diagram illustrating the system architecture for control components used in an apparatus of the present invention;

Figure 3 is a flow diagram illustrating the creation of an indexing network in accordance with the present invention;

Figures 4A, 5A and 6A illustrate an indexing network in creation;

Figures 4B, 5B and 6B illustrate localities of responsibility corresponding with the indexing nodes illustrated in Figures 4A, 5A and 6A;

Figures 7 to 10, 12 and 13 are flow diagrams illustrating functionality provided at individual nodes of the indexing network in accordance with the present invention; and

Figure 11 is a schematic drawing illustrating the routing of agent-finding requests within the indexing network of the present invention.

Referring to Figure 1, at the physical or bearer level the telecommunications environment of a user U1 in a particular locality comprises a cellular telephone, or a
5 personal digital assistant, T1 which may include a Global Positioning System Receiver and which is carried by the user; a facsimile apparatus T2 and conventional telephone T3; and a computer workstation T4.

The various terminals T1-T4 are each capable of receiving different signal formats, as follows:

- 10 T1 - voice or low bit rate data.
- T2 - facsimile image signals.
- T3 - narrow bandwidth audio.
- T4 - high bit rate data in various formats or any of the above.

In communication with the various terminals are a number of different
15 communications channels forming parts of different notional networks (although some or all may be commonly owned).

A public land mobile network (PLMN) (e.g. a GSM - compatible digital cellular network) N1 is connected via a base station B1 of the PLMN and a radio interface to terminal T1. The base station B1 provides a cell in the environment of
20 the area within which the user U1 is located.

A public switched telephone network (PSTN) N2 is connected via a local line to terminal T3, and via a local line to terminal T4.

A local area network (LAN) N3, including a LAN server is connected via a data link to terminal T3. Further terminals T6-T9 (not shown) at different distances
25 from the user are also connected in the LAN.

The user U1 carries an identifying device interacting with a location update device via which his position within the telecommunications environment may be tracked. For example, in this embodiment the identifying device comprises a chip carrying card or "smart card" carrying data identifying the user, and some or all of the terminals T1-T4 carrying a location update device in the form of a card reader arranged to read the card. Alternatively, it could comprise a 'smart badge' transponder, the location of which is tracked automatically.

Specifically, the terminals T1-T4 may carry such smart card readers to signal tracking information via the networks to which they are connected. Additional smart card readers are installed at access points to a building or area, and are connected, for example to the LAN N3, to signal a user's location.

Further, preferably, the terminal T1 comprises, in addition to cellphone communicating components, a location update device in the form of a global positioning system (GPS) receiver and is arranged to derive and signal its position, speed and direction from a GPS satellite S1 periodically as disclosed in EP 0467651 (Motorola). Alternatively, the cellphone T1 could perform positioning additionally using a land-based positioning signal, such as by differential GPS positioning, or purely using land-based positioning signals, such as differential GSM triangulation signals as described in WO 96/35306 (Telecom Securicor). The terminal T1 signals the user's location, speed and direction via PLMN N1.

Thus, the position of the user U1 is signalled by one or more of several means; firstly, it may be signalled from the terminal at which he has logged in, for example by password and/or by the insertion of his smart card; secondly, his geographical position may be signalled from a positioning signal receiver; and thirdly, his position within a building or area may be signalled from the access system. His

speed and direction may also be signalled from the positioning signal receiver. Alternatively, the user can communicate his location by calling using T1 or T2, in which case he may be identified by Calling Line Identity (CLI).

Each of the networks N1-N3 is connected, via gateways G1-G3
5 respectively, to a wide area network (WAN), such as the Internet, consisting of packet switches PS interconnected by high speed data links, such as asynchronous transfer mode (ATM) links.

The WAN provides connections, via the packet switches PS, to distributed information servers, such as Web servers WS, containing multi-media information
10 sources, such as Web pages. The WAN also provides access to distributed processing environment (DPE) Servers DS, which are connected to and distributed between the packet switches PS of the WAN.

The DPE Servers DS provide a distributed processing environment (DPE) which supports the interaction of software objects. The communication between
15 the objects may be handled by object request brokers (ORBs), such as provided by the object management group's common object request broker architecture (CORBA). Furthermore, the DPE Servers DS provide for persistent storage of the software objects held therein. This may be provided for example by ObjectStore's PSE (persistent storage engine) PRO (trademark).

20 Each of the DPE Servers DS stores intelligent software agents, as discussed in further detail below.

For the reasons described in the above referenced prior art, it is advantageous to employ a so called "agent based" control mechanism. The term "agent" has in the past been used with a number of different senses; here, except
25 where the context makes it clear that this is unnecessarily limiting, it will be

understood to mean an independently executing control program under control of which a computer or computer controlled switching centre performs the functions attributed to the "agent". The term is not necessarily limited to control programs which monitor their environment and adapt their behaviour and response thereto, but
5 encompasses such programs.

Each agent makes use of data, and it is convenient that the agents should therefore operate in "object-oriented" fashion; that is to say, that the data should be "encapsulated" so as to be accessible and alterable only by associated control programs, acting in response to "messages" (which need not, however, be physically
10 transmitted but could simply be data passed via the stack of a single computer). The agents are embodied by a mobile agent software system, such as IBM's "Aglets" (trademark) system, ObjectSpace's "Voyager" (trademark) system or suchlike. A discussion of mobile agents may also be found in "Mobile Agents", Lecture Notes in Computer Science, Rothermel K. Popescu-Zeletin Eds., First Int. Workshop, MA '97,
15 Berlin, April 1997.

Being mobile, the agents are able to access information either remotely, via the data links described, or locally, by moving themselves to the location of the information.

It will, however, be understood that the use of mobile agents and the object
20 oriented format is inessential to the invention.

Referring to Figure 2, the software architecture of the system includes a location updater object class 2, a terminal agent object class 4, a personal agent object class 6, an information agent object class 8 and a location index object class
10.

Each user in the system has a personal agent operating in the system on its behalf. Each information source in the system has at least one information agent operating in the system on its behalf. Each location update device in the system has a location updater object operating in the system on its behalf and to which its location updating signals are transmitted. Each terminal in the system has a terminal agent operating in the system on its behalf through which the terminal interacts with the distributed processing environment. Finally, a location indexing network has location index objects operating on its behalf.

Each agent and each of the location index objects includes a software code which is stored in the system. The relative locations of the agents within the system is not critical, since the agents are accessible by means of the networks N1-N3. However, in an advantageous arrangement, at least some of the terminal agents may be located on the respective terminals they represent and the location updaters may be held on a DPE server DS at the point of receipt of the location updating information sent via one of the networks N1-N3. The personal agents and information agents may be located on DPE servers holding the respective nodes of the location index with which they are interacting, as will be described in further detail below.

Each personal agent has data storage attributes for storing the following data:

1. Its user's preference data, including preferred categories of data to be accessed, age, gender, state of health, friends, interests, language preferences, information format type preferences, dynamic update preferences, location-based preferences, time/date-based preferences, cost limits on information retrieval, wildcard key words, etc.

2. An item details list detailing information sources, terminals offering service and users present in the current locality of the user.
3. A shortlist of selected item details already presented to the user.
4. System addresses of the user's personal terminals.
- 5 5. The identity of the terminal currently being used by the user.
6. The current location of the user.
7. The speed and direction in which the user is currently travelling.
8. An alternative location of interest to the user.
9. A selection algorithm for filtering information by reference to the user's
- 10 preference data.

The personal agent 6 interfaces with each of the location index, information agents 8, terminal agents 4 and location updater 2 as will be described below.

The information agent has data storage attributes for storing an item details object for the information source, to be described further below.

- 15 The terminal agent 4 has attributes for containing the following data:
 1. The system address of the terminal.
 2. The system address of the personal agent of the current terminal user.
 3. A shortlist of item details sent to the terminal by the current personal agent.
 4. The system address of the currently selected information source, if any.
 - 20 5. An item details object for the terminal, to be described in further detail below.
 6. A list of allowable input and output file formats.
 7. A list of file format translations which the terminal agent supports.

The location updater 2 has data storage attributes for containing the
25 following data:

1. The current location, and speed and direction if appropriate, of the corresponding location update device, such as the GPS receiver.
2. The identities of users, and the system addresses of their personal agents, being serviced by the location updater (multiple users if the location update device is
5 fixed, single user if the location update device is mobile).

Each location index object derived from the location index object class 10 forms a node of an indexing network, interconnected with related nodes of the indexing network.

Each node of the index has a locality index for storing item details objects
10 to be indexed on a locality basis, and a name index for storing item details objects and pointers to item details objects to be indexed by the name of the agent concerned. In addition, each node is provided with the following set and stored attributes:

1. A locality of responsibility (LOR), specified in the form of Cartesian
15 coordinates for its centre and parameters defining its size and shape.
2. A predefined level within the indexing network. The indexing network includes a root node at level 1, responsible for a large locality, and subnodes at levels 2 and above, responsible for localities which form sub-localities of that of the root node, and that of nodes above their level in the indexing network. It is to
20 be noted that, herein, "higher" level nodes have numerical designations which are smaller than that of "lower" level nodes.
3. References to nodes to which the node is related in the network, including one or more of parent nodes, children nodes, sibling nodes, uncle nodes, nephew nodes and cousin nodes.

Location index objects having different, and in particular spaced, localities of responsibility are stored on different of the DPE servers DS to allow very large scale scalability, by having a large number of DPE servers each handling a fraction of the data storage and retrieval operations of the system.

5 In order to create, or alter, an indexing network, new nodes are created at a particular level, and their attributes are set in accordance with data specified by a party responsible for the indexing network itself, as illustrated in Figure 3.

As a first step, the new nodes are instantiated, step 100. The new nodes are then defined within the indexing network by setting their locality of
10 responsibility (LOR), step 102, setting their level within the network, step 104, and setting the relationships of the new node and setting references to the new node in the previously existing nodes in accordance with their relationship within the network, step 106. The relationships are set by a new node querying its parent for the various adjacent relations which include contenders for relations of the new
15 node. The LORs of the nodes returned by the parent are analysed by the new node in order to decide whether to connect to them, in which case the new node stores the adjacent node in its relations database. It also informs the related node of its presence in order to establish reciprocal connections.

An indexing node network is constructed by functionality provided in the
20 location index object class by use of the following rules set:

1. If no tree currently exists, create a root node at level 1, by instantiating an instance of the location index object class.
2. If a node has a LOR which is itself insufficiently small for certain location-specific information, or if the node has a current processing load which exceeds a
25 set threshold, create one or more nodes which are responsible for sub-localities of

the locality for which that particular node, referred to herein as the splitting node, is responsible. If a plurality of new nodes which are adjacent are created, interconnect the new nodes via a sibling relationship, with the splitting node as their parent. Set each new node within the indexing network to the level of their
5 parent, plus 1.

3. If the splitting node has siblings or cousins, compare each new child node with the splitting node's siblings and cousins. If the localities of responsibility by the two nodes being compared are adjacent, create an uncle/nephew link between them. Set the depth of the relationship, being the comparative levels of the nodes,
10 to 1.

4. If the splitting node has one or more uncles, compare each new child node with each of the splitting node's uncles. If the localities of responsibility covered by the two nodes being compared are adjacent, create an uncle/nephew link between them. Set the depth of the link equal to the depth of the matching uncle
15 relationship, plus 1. These related nodes are referred to herein as great-uncles.

5. If the splitting node has one or more nephews with depths N where $N > 1$, being a great-uncle/nephew relationship, compare the locality of responsibility set for each new child node with that of the splitting node's nephews. If the two nodes are adjacent, set an uncle/nephew link between them with a depth of $N-1$.

20 6. If the splitting node has one or more nephews with depth 1, compare the locality of responsibility of each new child node with that of each of the splitting node's nephews. If the areas covered by the two nodes are adjacent, create a cousin link between them.

The operation of these rules is illustrated with reference to Figures 4 to 6.

Referring to Figure 4A, which illustrates an indexing network at an early stage in creation, the indexing network includes a root node 110 which has a locality of responsibility corresponding to the entire geographical coverage of the indexing network, illustrated in Figure 4B as outer rectangle 112. The network level of the root node 110 is 1. The root node 110 only has children relationships.

The child nodes 114 each have a locality of responsibility which forms a subset of the locality of responsibility of the root node 110, illustrated by inner rectangles 116 in Figure 4B. The child nodes are created using rule 2 described above applied to the root node 110.

Referring to Figure 5A, one of the child nodes 114D may be split to provide further child nodes 118A-D, which are grandchildren of the root node 110. The new child nodes 118A-D have localities of responsibility which form sub-localities 120A-D of the locality of responsibility 116D of their immediate parent node 114D, and consequently also form sub-localities of the locality of responsibility 112 of the higher level node 110.

The relationships of the new nodes 118A-D are set by defining sibling relationships between each of the new nodes 118A-D, parent/child relationships with the parent node 114D, and, where the localities of responsibility 120A-D of the new nodes 118A-D are adjacent to the localities of responsibility of higher nodes in the network, uncle/nephew relations are set by references to those higher level nodes 114A-C. These uncle/nephew relationships are set in accordance with rule 3 above.

Referring to Figures 6A and 6B, a node 114C adjacent to the previously split node 114D may also be split to produce four new children nodes 118E-H. These new children nodes have localities of responsibility which are set to be sub-

localities of the locality of responsibility 116C of their immediate parent node 114C. Their level in the network is set at 3, in accordance with rule 2 above. Their relationships within the indexing network include parent/child relationships with the parent node 114C, uncle/nephew relationships with nodes 114A, B, D at
5 the same level as their parent node 114C and sibling relationships between each of the new nodes 118E-H. In addition, the new nodes 118E-H which have localities of responsibility 120F, H which adjoin the localities of responsibility of the previously created nodes 118A, C at the same level are defined to have cousin relationships with those previously created nodes, in accordance with rule 6 above.

10 In each of Figures 4A, 5A and 6A, parent/child relationships are illustrated with bold, solid, arrowed lines. Sibling relationships are illustrated with solid, arrowed lines. Uncle/nephew relationships are illustrated with closely spaced dashed, arrowed lines. Cousin relationships are illustrated with spaced dashed, arrowed lines.

15 Figures 4 to 6 illustrate the principle of construction, and the division of the localities of responsibility of an indexing network, by means of nodes at a plurality of levels below the root node level. As the network is increased further in depth, the localities of responsibility for nodes defined at each next lower level becoming progressively smaller, such that the indexed information, to be described
20 below, at each node becomes increasingly location-specific. This structure allows agents interacting with the indexing network to index information at a certain level of location specificity, and to obtain information at a certain level of location specificity, to thereby provide a level of detail appropriate to the information storage act or information retrieval act being performed.

It is to be understood that the rectangular localities of responsibility illustrated in Figures 4B, 5B and 6B are examples only. The localities may be defined as other two dimensional shapes, and may also be defined as three dimensional volumes. The node splitting procedures may also have different, or
5 variable, cardinalities.

Figure 7 is a flow chart illustrating the functionality provided at each node, by the location index object class, for allowing information agents to index location-specific data in the nodal network.

Each information source has a node in the indexing network with which
10 the information agent is set to interact, referred to herein as a gateway node. In order to index an information source for which the information agent is acting, the information agent transmits an advertise-in-locality request to its gateway node, passing across its item details object with the advertise request.

The item details object held in an information agent includes:

- 15 1. The gateway node at which the information agent is currently set to communicate with the indexing network.
2. The name of the information source.
3. Data specifying a locality of pertinence (LOP) of the information held on the information source for which the information agent is acting. The locality is
20 specified in the form of Cartesian coordinates and parameters defining its size and shape.
4. Meta-information concerning the information stored in the information source, including a list of the files contained in the information source, format identifiers (for example Multipurpose Internet Multimedia Extension (MIME) records),
25 the sizes of the files, the language (for example English) of a text file, encoding

identifiers, a best before date and a priority indication indicating the relative importance of the respective files in the information source.

5. The system address of the information source. In the case of an information source in the form of a Web page, this consists of a Uniform Resource Locator (URL).

When an advertise-in-locality request is received, by a node, step 200, the node applies a heuristic function method to the LOP in the passed item details object, to determine whether the LOP intersects with its locality of responsibility of the node, step 202. If there is no intersection, the node passes the request, along with the item details object, to its parent node, step 204.

If the LOP and the LOR are found to intersect, the node proceeds to apply a further heuristic function to determine whether the LOP of the information source and the LOR of the node are similar in size, step 206. Here, "similar in size" includes a range of similarity in size, which is dependent primarily on the interval in size between the LORs of nodes at different levels in the indexing network. For example the similarity function may be arranged such that the size of the LOP may range from midway between the size of the node's LOR and the size of the LOR of the parent node down to midway between the size of the node's LOR and the size of the LOR of the child node of the node in question in order for the LOP and LOR to be considered similar in size. Thus, where child nodes are formed by quartering in an indexing network, the range in size for which the information source's LOP is considered to be similar in size to that of the node's LOR could range from of the order of twice the size of the LOR down to of the order of half of the size of the LOR.

If the LOP is found not to be similar in size in accordance with the similarity function applied, it is determined whether the LOR is significantly larger, step 208. If so, the advertise request, along with the item details object, is passed to each of the node's children which have an LOR intersecting with the LOP of the request, step 210. If no children currently exist for the node, the items details are indexed at the current node, to be passed down if the node subsequently divides.

Otherwise, the request is passed to the parent of the node, step 212. As the parent node has a locality of responsibility which includes that of the upwardly passing node, the parent node, or other parent nodes higher up in the indexing network will be able to accept the advertise-in-locality request.

If in step 206 the locality of pertinence and the locality of relevance are found to be similar in size by the node receiving the advertise request, the node places the item details object in its locality index, to be stored for future retrieval by personal agents interacting with the indexing network, step 214.

The item details object for an information source contains an attribute which specifies a propagation characteristic of the information. Namely, this propagation attribute specifies whether the advertise request is to be propagated to a level below the level at which the LOP and LOR are similar in size, and if so, the number of levels to which the item details are to be propagated. Thus, the item details are provided with one of the following possible propagation categories:

1. Propagate fully. The item details are passed down to be indexed at child nodes at every level in the network below the node at which the LOP and LOR are similar in size.

2. Bounded-propagate. The item details are passed down to be indexed at child nodes at every level until a more location-specific information source relating to the same subject-matter is indexed.

3. Normal. Such item details are not propagated down the indexing network.

5 To give an example, information such as health and safety notices for a building may be defined with a locality of pertinence corresponding with the whole area of the building, and a bounded-propagate property, such that the item details for the information source will be passed down the indexing network until a node covering a more specific locality, such as for example a laboratory room, at which
10 more specific health and safety instructions are required.

As a further example, notices regarding the opening times of a building may be defined to have a locality of pertinence corresponding with that of the building, and with a propagate fully property, so that such a notice is passed down to all nodes having localities of responsibility within the building. On the other
15 hand, high level information, such as the location of the building in the context of a larger site, may be defined with a locality of pertinence equal to that of the building, and a normal category, so that the information is only accessible at nodes having localities of responsibility which are relatively large.

Thus, the item details are propagated down the indexing network in
20 accordance with the specified propagation characteristics, steps 216 and 218.

Next, in step 220, the node initially in receipt of the advertise request checks the localities of responsibility of its related nodes which have adjacent localities of responsibility, in order to determine whether the LOP specified in the item details object intersects with the LOR or these adjacent nodes. If so, the
25 node passes the advertise request to the adjacent nodes having intersecting LORs,

step 222. These adjacent nodes then proceed to step 206 in the procedure illustrated in Figure 7.

By repeating the procedure illustrated in Figure 7 for each information agent, the indexing network nodes are populated with item details objects at the
5 appropriate locational specificity.

Once the locality indexes of the indexing network is populated with item details objects, the corresponding information sources may be accessed by personal agents in a location-specific manner in accordance with the procedure illustrated in Figure 8.

10 In order to access the indexing network, a personal agent transmits a what-is-here? request to a gateway node in the indexing network with which the personal agent is set to interact, passing across data defining a locality of interest (LOI) of the user for which the personal agent is acting. This locality is specified in the form of Cartesian coordinates and parameters defining its size and shape.

15 The LOI of the user may be obtained in two ways. First, the user may specify a locality of interest via the terminal which the user is currently using, which is then passed on to the user's personal agent. This locality of interest is not necessarily related to the current location of the user.

Secondly, an LOI may be derived from the tracking information received
20 from a location updater device, via the corresponding location updater object, which provides the current location, speed and direction of travel of the user. The LOI may be derived from each of these parameters. In the case of a stationary user, the LOI is defined by default to be centred at the current location of the user, and to have a size equal to the locality of responsibility of the lowest level node in
25 the indexing network which covers the current location of the user, thereby to

ensure access to the most location-specific information. The stationary user may however request, via their current terminal, a locality of interest which is larger than this default LOI. The LOI of the stationary user is defined by default to have a circular outline.

5 In the case of a travelling user, the speed and direction characteristics signalled by the user's location updater device is used to define the user's LOI differently. Namely, the LOI is centred at a point offset from the current location of the user in the direction of travel of the user, the distance increasing with the speed of travel of the user. The size of the locality of interest of the user is also
10 increased, to increase the level of generality of the information derived from the indexing network. Finally, the shape of the LOI is altered to extend the LOI to a greater extent in the direction of travel of the user than in a direction normal to the direction of travel.

 The setting of the LOI of the user is carried out by the user's personal
15 agent, which is continually updated with the user's current location, speed and direction of travel. In the case of a mobile location updater, such as the positioning signal receiver described above, a location update message is transmitted to the personal agent when the user carrying the location updater device moves a predefined threshold distance since a previous location update.
20 The personal agent proceeds to generate a what-is-here? request when the location of the user has altered a significant degree in relation to the size of the user's current LOI.

 Referring again to Figure 8, on receipt of the what-is-here? request, the receiving node applies an intersection function method to the LOI passed in the
25 request, to determine whether the LOI intersects with the LOR of the node, step

302. If there is no intersection, the receiving node passes the request, along with the LOI of the request, to its parent node, step 304. Alternatively, if there is no intersection the node may compare the LOI with the LOR of any related adjacent nodes, passing the request to the best locality match, or passing the request to the parent if no good match is found.

If the LOP and the LOI are found to intersect, the node proceeds to apply a similarity function, such as that described in relation to Figure 7, to determine whether the LOI of the user and the LOR of the node are similar in size, step 306.

If the LOI is found not to be similar in size in accordance with the similarity function applied, it is determined whether the LOR is significantly larger, step 308. If so, the what-is-here? request, along with the specified LOI, is passed to each of the node's children which have an LOR intersecting with the LOI of the request, step 310.

Otherwise, the LOI is significantly larger in size than the LOR, and the request is passed to the parent of the node, step 312. As the parent node has a locality of responsibility which includes that of the upwardly passing node, the parent node, or other parent nodes higher up in the indexing network will be able to accept the what-is-here? request.

If the LOI of the user and the LOR of the node subject to the request are similar in size, the receiving node further determines whether the user's LOI intersects with the LORs of its related nodes which exist at the same level in the indexing network, being either sibling nodes or cousin nodes, step 314.

If the LOI also intersects with the LORs of any adjacent nodes of equal level, the receiving node transmits a what-is-here? request to each of the found adjacent nodes, step 316. These selected nodes return an item details list

consisting of the item details objects stored in their locality indexes, step 318. The receiving node then proceeds to construct a full item details list which includes the item details objects from adjacent nodes having LORs which intersect with the LOI specified in the original request, and the item details objects held in
5 its own locality index, step 320.

If the node finds no adjacent nodes with LORs which intersect with the LOI of the user, the item details list to be transmitted consists of item details objects held solely in the receiving node's locality index.

Finally, the item details list is passed to the requesting personal agent,
10 step 322.

On receipt of an item details list, the personal agent performs its selection algorithm, using the user's preference data, in order to filter out information objects representing information sources which are considered to be of low potential interest to the user, and to produce a shortlist of the remaining
15 information objects which are transmitted to the terminal agents of the terminal currently serving the user, for the presentation of summary information to the user at their terminal. On reviewing the summary information, the user is able to select information sources which are of interest, and access information held in the information sources, by means of the system address for the information source
20 specified in the corresponding information object now held in the terminal agent.

Information agents may be configured to act on behalf of terminals accessible within the geographical area covered by the indexing network. In this manner, a personal agent acting on behalf of the user may locate terminals, using a what-is-here? request, to identify terminals accessible in the immediate locality
25 of the user. Furthermore, the information stored in the corresponding item details

object representing the terminal may specify the formats of data and transmission protocols accepted by the terminal, thereby allowing the personal agent to select a terminal appropriate for a particular type or format of information to be received by the user.

5 In addition to information agents and terminal agents, personal agents may also advertise within the indexing network. In order to do this, each personal agent is provided with an item details object to pass over to the indexing network for indexing at an appropriate level. The item details object for the personal agent include the following data storage attributes:

- 10 1. The gateway node at which the personal agent is currently set to communicate with the indexing network.
2. The name of the user.
3. The current location of the user.
4. A locality of pertinence (LOP) for the user. This may be derived either
15 from the locality of interest (LOI) currently set for the user, which is dependent on the current location, speed and direction of travel of the user, and/or may include a "home" locality of pertinence for the user. The locality is specified in the form of Cartesian coordinates and parameters defining its size and shape.
5. An e-mail address for the user.
- 20 6. A current address for the personal agent.
7. A system address for an information source associated with the user, for example the URL of a personal Web page.

 In order to index its information details object by locality, the personal agent transmits an advertise-in-locality request containing the item details object to
25 the personal agent is gateway node, which then proceeds with the steps described

in relation to Figure 7 in order to index the user's personal item details object within the indexing network.

The indexing network is provided with a name index, consisting of individual databases distributed between the nodes of the network. In order to
5 feature in the name index, an agent transmits an advertise-by-name request to its gateway node.

Figure 9 illustrates the procedure followed by a gateway node in receipt of an advertise-by-name request from an agent previously not indexed in the system. Along with the request, the agent passes its current item details object to the
10 node. On receipt, step 400, the gateway node stores the passed item details object, in its name index, step 402. A request to add a pointer, associated with a unique name for the agent, is passed to the parent node, step 404. The parent node adds this pointer to its name index, and then passes a similar request to its parent node, which repeats the same until the root node is reached.

15 Thus, when an agent is advertised-by-name within the indexing network, a reference to the gateway node will be present at a directly related node at each level in the indexing network above the gateway node, at which the agent's item details object is held.

In order to find an agent, the procedure illustrated in Figure 10 is followed
20 by a node requested to find the agent by name, step 500. The request need only contain the unique name of the agent.

If a reference to the agent identified by the unique name in the find-by-name request is not present in the name index of the node receiving the request, step 502, it passes the request directly to its parent, step 504, which proceeds
25 from step 500.

Once a node in receipt of a find-by-name request does have a reference to the identified agent in its name index, unless the node is the gateway node, step 506, it passes the request to the node immediately below it identified by the pointer held in its name index, step 508. Once the request reaches the gateway node, it returns the system address of the agent to the original requesting party, step 510.

Figure 11 illustrates the way in which the name index feature operates. In the example shown, a first agent, Ag1 is set with a gateway node at level 2, node 114A. Second, third and fourth agents, Ag2, Ag3 and Ag4 are set with gateway nodes at level 3, nodes 118D, 118A and 118E, respectively.

Figure 11 illustrates each of agents Ag1, Ag3 and Ag4 attempting to find a reference to agent Ag2 in the network. Agent Ag3 is set with a gateway node which is a sibling node of the gateway node which agent Ag2 is set to, and the find-by-name request transmitted by agent Ag3 to its gateway node is propagated only to its parent node, at which a pointer to agent Ag2 will be found in the name index of the node.

The find-by-name request transmitted by agent Ag1 will be passed from its gateway node, node 114A, to the root node 110, at which point a pointer to the item details object of agent 2 is present in a name index.

A find-by-name request transmitted by agent Ag4 to its gateway node, node 118E, will be passed on by that node, and the parent node 114A, in turn, which each do not have references to agent Ag2 within their name indexes. The find-by-name request is then passed down from the root node 110 in accordance with the pointers stored in the name indexes of the handling nodes, until it reaches

the gateway node of agent Ag2, which returns the system address of agent Ag2 to agent Ag4.

Thus, each of the categories of agent which interact directly with the indexing network, being the information agent, the personal agent and the terminal agent, are set to communicate with a particular gateway node of the indexing network. As the indexing network consists of a distributed network which extends over a plurality of distributed computing nodes, such as the DPE Servers DS described in relation to Figure 1, and since the agents in question may be mobile, a procedure is defined whereby an agent may move and alter the gateway node with which the agent is set to communicate.

The gateway node moving procedure may be initiated either by the agent itself or by a node of the indexing network. For example, if an agent detects that response delays in communications with the currently set gateway node have become excessive, the agent may initiate a move to a node having a locality of responsibility which is closer to, or intersecting with, the locality of pertinence or locality of interest of the agent. Alternatively, if a particular node of the indexing network detects overloading, it may instruct certain of the agents currently communicating with the node as a gateway node to move to an adjacent node.

Figure 12 illustrates the steps carried out by the gateway node of an agent on receipt of a move-node request from the agent, step 400.

The gateway node first determines whether the LOI or LOR of the requesting agent intersects with the LOR of an adjacent node, step 402. If no such intersection exists, the gateway node passes the request to its parent node, step 404.

Otherwise, the gateway node passes the move-node request to the most appropriate adjacent node having an LOR which intersects with the LOP or LOI of the requesting agent.

Referring to Figure 13, when a particular node receives a move-node
5 request for an agent from another node, step 700, the receiving node first determines whether the agent specified in the move-node request is advertising within the indexing network by name, step 702. This information will be found in the item details object passed with the move-node request, which item details object contains a flag indicating whether or not the agent is advertising-by-name.

10 If the agent is advertising-by-name, it is necessary to ensure the consistency of the name indexes when an agent is moving. Accordingly, the receiving node places the item details object within its own name index, step 704. The receiving node must also initiate a process whereby the name indexes of other nodes are updated, step 706. The receiving node follows the following rules when
15 updating the name indexes of other nodes:

1. If the move-node request is received from a parent node, no updating is required.
2. If the move-node request is received from a child node, the receiving node transmits a remove-by-name request to the sending node, which results in the
20 deletion of the corresponding item details object from the sending node's name index.
3. If the move-node request is received from a sibling node, the receiving node transmits a remove-by-name request to the sending node, and transmits a request to its parent to update the pointer in its name index.

4. If the move-node request is received from a cousin node, the receiving node transmits a remove-by-name request to the sending node, and transmits a request to its parent node to add a pointer in its name index and to propagate the request upwards until a previous entry for the agent is found, and thence to
- 5 propagate a request downwards to remove all previous pointers which are now incorrect.
5. If the move-node request is received from an uncle node, the receiving node transmits a remove-by-name request to the sending node. The receiving node also transmits an advertise-by-name request its parent nodes including a
- 10 request to add and update name index pointers which is propagated up to and including $N + 1$ nodes above the receiving node's location, where N is the depth of the uncle minus the depth of the receiving node.
6. If the move-node request is received from a nephew node, a request is sent to the node's parent to update the pointer in the parent node's name index.
- 15 A remove-by-name request is transmitted to the sending node, including a request for the removal of pointers from the name indexes of the sending node's parents to a level of N above the sending node where N is the depth of the nephew node minus the depth of the receiving node.

Once the name indexes of the other nodes in the network are updated, the

20 receiving node applies the intersection function to determine whether the locality passed in the request intersects with the LOR of the receiving node, step 708. This is not necessarily the case, if the request was received from a child node. If no intersection is present, the move-node request is passed on to a more appropriate node, which is determined as per step 602 described in relation to

25 Figure 12, step 710.

If an intersection is found to occur, the receiving node applies a size similarity function to determine whether the locality passed in the move-node request is similar in size to its own LOR, step 712. If not, the node determines whether its LOR is significantly larger than the passed locality, step 714, and if so
5 it passes the move-node request to a child node with an intersecting LOR, step 716. Otherwise, the move-node request is passed upwards to the parent node, step 718.

Finally, if the node receiving the move-node request is an appropriate gateway node, the requesting agent is informed of the system address of the new
10 node with which the agent is now set to communicate, step 720.

CLAIMS

1. A method of storing and/or retrieving location-based information, the method comprising:

storing, in a distributed network of data storage devices accessible
5 simultaneously from a plurality of remote user terminals, data defining a plurality of first localities in relation to which information storage is accessible; and

selecting ones of said first localities to represent second localities for which information is to be stored and/or retrieved such that:

- i) said first and second localities bear a predetermined locational
10 relationship; and
- ii) said first and second localities bear a predetermined relationship in size.

2. A method according to claim 1, wherein said first localities are
15 selected such that said first and second localities share at least one geographical location.

3. A method according to claim 1 or 2, wherein said first localities are
selected such that said first and second localities are similar in size.
20

4. A method according to claim 1, 2 or 3, wherein said data defines access nodes which include a node representing a relatively large locality and one or more nodes representing one or more relatively small localities which overlap said relatively large locality.

5. A method according to claim 4, wherein a plurality of said nodes representing relatively small localities form divisions of said relatively large locality.

6. A method of storing location-based information, the method
5 comprising:

defining, in a distributed network of data storage devices accessible simultaneously from a plurality of user terminals, a plurality of data access nodes each of which is responsible for a predefined locality, said plurality of nodes including a higher level node responsible for a larger locality and lower level nodes
10 responsible for smaller localities which overlap said larger locality,

indexing references to information sources containing locality-specific information at said data access nodes, different information source references being indexed at said higher level node than at said lower level nodes; and

transmitting said references from said data access nodes on request.
15

7. A method according to claim 6, wherein at least one information source reference is commonly indexed at said higher level node and said lower level nodes.

20 8. A method of storing location-based information, the method comprising:

defining, in a distributed network of data storage devices accessible simultaneously from a plurality of user terminals, a plurality of data access nodes each of which are responsible for a predefined locality;

indexing references to information sources containing locality-specific information at said data access nodes, one or more of such references being repeatedly indexed at different of said nodes; and

transmitting said references from said data access nodes on request.

5

9. A method according to any of claims 4 to 8, wherein said nodes are interlinked in a network structure.

10. A method according to claim 9, wherein said network structure is a hierarchical structure.

11. A method according to claim 10, wherein said nodes are interlinked in parent/child relationships.

12. A method according to claim 10 or 11, wherein said nodes are interlinked in sibling relationships.

13. A method according to claim 10, 11 or 12, wherein said nodes are interlinked in uncle/nephew relationships.

20

14. A method according to claim 10, 11, 12 or 13, wherein said nodes are interlinked in cousin/cousin relationships.

15. A method according to any of claims 11 to 14, wherein said interlinking comprises a node holding a reference whereby the related node may be accessed.

5 16. A method according to any of claims 4 to 15, wherein said nodes are distributed amongst said data storage devices.

17. Apparatus for storing location-based information in accordance with the method of any of claims 1 to 16.

10

18. A method of retrieving information for presentation to a user, the method comprising:

defining a locality of interest to the user in dependence on both a location of the user and a speed of travel of the user; and

15 selecting, in a distributed network of data storage devices accessible simultaneously from a plurality of user terminals, information sources from which locality-specific information may be retrieved, on the basis of the defined locality of interest.

20 19. A method according to claim 18, wherein the extent of the locality of interest of the user is altered in dependence on the speed of travel.

20. A method according to claim 19, wherein the extent of the locality of interest increases with the speed of travel.

25

21. A method according to any of claims 18 to 20, wherein the locality of interest is altered in dependence on the direction of travel of the user.

22. A method according to any of claims 18 to 21, comprising deriving
5 parameters relating to the travel of the user from a positioning signal receiver travelling with the user.

23. A method according to any of claims 18 to 22, comprising performing said selection in the apparatus of claim 17.

10

24. A method according to any of claims 1 to 16 or 18 to 23, wherein said network of data storage devices comprises a plurality of servers interconnected by data links and forming a distributed processing environment.

15 25. Apparatus for storing location-based information, said apparatus comprising a distributed network of data storage devices accessible simultaneously from a plurality of user terminals and defining data access nodes which are referentially interlinked, each said data access node being provisioned with a locality for which it is responsible and means for comparing the size of an input
20 locality in relation to which information storage is to be accessed and a locality for which the node is responsible.

26. Apparatus according to claim 25, wherein said apparatus is reconfigurable by the addition of, or the removal of, one or more of said data

access nodes, so as to transfer responsibility from or to one or more other nodes with localities of responsibility sharing at least one geographical location.

AMENDED CLAIMS

[received by the International Bureau on 13 October 1999 (13.10. 99);
original claims 1, 6, 8, 18 and 25 replaced by new claims 1, 6, 8, 18 and 25 remaining claims
unchanged (4pages)]

1. A method of storing and/or retrieving location-based information, the
method comprising:

storing, in a distributed network of data storage devices accessible
5 simultaneously for users at a plurality of remote user terminals, data defining a
plurality of first localities in relation to which information storage is accessible; and
selecting ones of said first localities to represent second localities for
which information is to be stored and/or retrieved such that:

- i) said first and second localities bear a predetermined locational
10 relationship; and
ii) said first and second localities bear a predetermined relationship in
size.

2. A method according to claim 1, wherein said first localities are
15 selected such that said first and second localities share at least one geographical
location.

3. A method according to claim 1 or 2, wherein said first localities are
selected such that said first and second localities are similar in size.

20

4. A method according to claim 1, 2 or 3, wherein said data defines
access nodes which include a node representing a relatively large locality and one
or more nodes representing one or more relatively small localities which overlap
said relatively large locality.

25

5. A method according to claim 4, wherein a plurality of said nodes representing relatively small localities form divisions of said relatively large locality.

6. A method of storing location-based information, the method
5 comprising:

defining, in a distributed network of data storage devices accessible simultaneously for users at a plurality of user terminals, a plurality of data access nodes each of which is responsible for a predefined locality, said plurality of nodes including a higher level node responsible for a larger locality and lower level nodes
10 responsible for smaller localities which overlap said larger locality,

indexing references to information sources containing locality-specific information at said data access nodes, different information source references being indexed at said higher level node than at said lower level nodes; and

transmitting said references from said data access nodes on request.
15

7. A method according to claim 6, wherein at least one information source reference is commonly indexed at said higher level node and said lower level nodes.

20 8. A method of storing location-based information, the method comprising:

defining, in a distributed network of data storage devices accessible simultaneously for users at a plurality of user terminals, a plurality of data access nodes each of which are responsible for a predefined locality;

15. A method according to any of claims 11 to 14, wherein said interlinking comprises a node holding a reference whereby the related node may be accessed.

5 16. A method according to any of claims 4 to 15, wherein said nodes are distributed amongst said data storage devices.

17. Apparatus for storing location-based information in accordance with the method of any of claims 1 to 16.

10

18. A method of retrieving information for presentation to a user, the method comprising:

defining a locality of interest to the user in dependence on both a location of the user and a speed of travel of the user; and

15 selecting, in a distributed network of data storage devices accessible simultaneously for users at a plurality of user terminals, information sources from which locality-specific information may be retrieved, on the basis of the defined locality of interest.

20 19. A method according to claim 18, wherein the extent of the locality of interest of the user is altered in dependence on the speed of travel.

20. A method according to claim 19, wherein the extent of the locality of interest increases with the speed of travel.

25

21. A method according to any of claims 18 to 20, wherein the locality of interest is altered in dependence on the direction of travel of the user.

22. A method according to any of claims 18 to 21, comprising deriving
5 parameters relating to the travel of the user from a positioning signal receiver travelling with the user.

23. A method according to any of claims 18 to 22, comprising performing said selection in the apparatus of claim 17.

10

24. A method according to any of claims 1 to 16 or 18 to 23, wherein said network of data storage devices comprises a plurality of servers interconnected by data links and forming a distributed processing environment.

15 25. Apparatus for storing location-based information, said apparatus comprising a distributed network of data storage devices accessible simultaneously for users at a plurality of user terminals and defining data access nodes which are referentially interlinked, each said data access node being provisioned with a locality for which it is responsible and means for comparing the size of an input
20 locality in relation to which information storage is to be accessed and a locality for which the node is responsible.

26. Apparatus according to claim 25, wherein said apparatus is reconfigurable by the addition of, or the removal of, one or more of said data




FIG. 1

2 / 10




FIG. 2




FIG. 3

3 / 10




FIG. 4A




FIG. 4B




FIG. 5A




FIG. 5B

5 / 10




FIG. 6A




FIG. 6B

6 / 10




FIG. 7

7 / 10




FIG. 8

8 / 10




FIG. 9




FIG. 10

9 / 10




FIG. 11




FIG. 12

10 / 10




FIG. 13